

LAMFLOOR®

Natural Engineered Wood Flooring
& Roof Decking



Architectural Quality & Structural Performance



- Unique wide boards with an authentic rustic look
- Floor or roof sheathing not required¹
- Span up to 48" on floor joists and 72" on roof rafters²
- LAMFLOOR on loft joists serves as both floor and ceiling
- Available in 3 appearance grades: A/A for lofts, C/A for ceilings, A/C for floors
- Northeastern Jack Pine, kiln-dried to 6-8% m.c.
- For interior use
- All boards identically sized
- Saves labor and materials
- Limited Lifetime Warranty³

ECO-FRIENDLY

The process used to make LAMFLOOR wide boards generates zero waste - everything from rejected raw materials to saw dust is recycled. And, by laminating and finger jointing small size lumber into bigger boards, we reduce the need to cut larger trees.

www.LAMCOewp.com

DESCRIPTION

LAMFLOOR® is wide board wood flooring produced by LAMCO Forest Products using the patented Lamlock fabrication process. Small size lumber used to make LAMFLOOR is first dried at low temperature with controlled moisture content. The pieces are then laminated and finger jointed into bigger boards. This process provides unparalleled dimensional stability.

Northeastern Jack Pine


- Similar to white pine, but more dense
- Has a beautiful wood grain
- Easy to stain or finish

Black Spruce^{4,5}

- Stronger, available in MSR lumber
- Longer spans than with Jack Pine
- Can replace steel roof decking

DIMENSIONS

Nominal	Actual	Exposed Width	Length	Coverage by Piece
2" x 12"	1 1/4" x 10 3/4"	10 1/2"	12'	10.5 sq ft
			16'	14.0 sq ft
			24' ⁴	21.0 sq ft



1. Subfloor required for concrete.
2. See www.LAMCOewp.com for span tables.
3. LAMCO warrants LAMFLOOR to be free of manufacturing defects for the life of the building when used and protected according to LAMCO's recommendations.
4. Available by special order only.
5. Contact LAMCO at (418) 679-2121 for more information.

FINISH

- LAMFLOOR is sold unfinished. To increase its durability, sand and apply varnish or an oil finish to the floor.
- Given its rustic floor character, LAMFLOOR flooring can contain natural defects that may require final touch-ups.

HANDLING AND STORAGE

- **Must always be stored inside.**
- To minimize expansion or shrinking in the floor, maintain relative humidity between 40% and 55%.
- Keep LAMFLOOR at room temperature for at least 72 hours prior to installation.

INSTALLATION

- Apply a 10" bead of construction adhesive to the joists.



- Place the LAMFLOOR board on the joists.



- Fasten to each joist with a 2 1/4" screw in the tongue. For easier fastening, predrill holes in the tongue.



(418) 679-2121
www.LAMCOewp.com

DISTRIBUTED BY:

Timberhaven Log & Timber Homes
 Phone: 855-306-5678
 Email: andrewharter@timberhavenloghomes.com